



6DT6

SHARP-CUTOFF PENTODE

7-PIN MINIATURE TYPE
For FM detector service

6DT6

GENERAL DATA

Electrical:

Heater, for Unipotential Cathode:

Voltage (AC or DC)	6.3 ± 10%	volts
Current	0.3	amp

Direct Interelectrode Capacitances
(Approx.):⁰

Grid No.1 to plate.	0.02	μf
Grid No.1 to cathode & internal shield, grid No.3, grid No.2, and heater.	5.8	μf
Grid No.3 to plate.	1.4	μf
Grid No.1 to grid No.3.	0.1	μf
Grid No.3 to cathode & internal shield, plate, grid No.2, grid No.1, and heater.	6.1	μf

Characteristics, Class A₁ Amplifier:

Plate Supply Voltage.	150	volts
Grid-No.3 Supply Voltage.	0	volts
Grid-No.2 Supply Voltage.	100	volts
Cathode Resistor.	560	ohms
Plate Resistance (Approx.).	0.15	megohm
Transconductance, Grid No.1 to Plate. . .	800	μmhos
Transconductance, Grid No.3 to Plate. . .	515	μmhos
Plate Current	1.1	ma
Grid-No.2 Current	2.1	ma
Grid-No.1 Voltage (Approx.) for plate μa = 10	-4.5	volts
Grid-No.3 Voltage (Approx.) for plate μa = 10	-3.5	volts

Mechanical:

Operating Position. Any

Maximum Overall Length. 2-1/8"

Maximum Seated Length 1-7/8"

Length, Base Seat to Bulb Top (Excluding tip) . 1-1/2" ± 3/32"

Diameter. 0.650" to 0.750"


Dimensional Outline See General Section

Bulb. T5-1/2

Base. Small-Button Miniature 7-Pin (JEDEC No.E7-1)

Basing Designation for BOTTOM VIEW. 7EN

Pin 1-Grid No.1
Pin 2-Cathode,
Internal
Shield
Pin 3-Heater



Pin 4-Heater
Pin 5-Plate
Pin 6-Grid No.2
Pin 7-Grid No.3

← Indicates a change.

6DT6



6DT6

SHARP-CUTOFF PENTODE

FM DETECTOR SERVICE

→ **Maximum Ratings, Design-Maximum Values:**

PLATE VOLTAGE.	330 max. volts
GRID-No.3 (SUPPRESSOR-GRID) VOLTAGE. . . .	28 max. volts
GRID-No.2 (SCREEN-GRID) SUPPLY VOLTAGE . .	330 max. volts
GRID-No.2 VOLTAGE.	See Grid-No.2 Input Rating Chart at front of Receiving Tube Section
GRID-No.1 (CONTROL-GRID) VOLTAGE:	
Positive-bias value.	0 max. volts
GRID-No.2 INPUT:	
For grid-No.2 voltages up to 165 volts . .	1.1 watts
For grid-No.2 voltages between 165 and 330 volts.	See Grid-No.2 Input Rating Chart at front of Receiving Tube Section
PLATE DISSIPATION.	1.7 max. watts
PEAK HEATER-CATHODE VOLTAGE:	
Heater negative with respect to cathode.	200 max. volts
Heater positive with respect to cathode.	200 [▲] max. volts

Maximum Circuit Values:

Grid-No.1-Circuit Resistance:

For fixed-bias operation	0.25 max. megohm
For cathode-bias operation	0.5 max. megohm

° With external shield JEDEC No.316 connected to cathode.

▲ The dc component must not exceed 100 volts.


→ Indicates a change.



6DT6

6DT6

AVERAGE PLATE CHARACTERISTICS



TUBE DIVISION
RADIO CORPORATION OF AMERICA, HARRISON, NEW JERSEY


92CM-8827

6DT6



6DT6

AVERAGE PLATE CHARACTERISTICS




6DT6



6DT6

AVERAGE CHARACTERISTICS



TUBE DIVISION
 RADIO CORPORATION OF AMERICA, HARRISON, NEW JERSEY


92CM-8829



6DT6

6DT6

AVERAGE CHARACTERISTICS




6DT6



6DT6

AVERAGE CHARACTERISTICS



TUBE DIVISION
 RADIO CORPORATION OF AMERICA, HARRISON, NEW JERSEY

92CM-8825